

HEAT SHRINKABLE TUBING

Heat shrinkable tubing material is a hand new high-tech product. It owns excellent physical and chemical character, rotten-resistance, insulation, cooling, hindering burning function. It provides a high-tech insulation protection material for electric and communication engineering. It fits for insulation of wire cable, cable terminal and joint, It protects and marks for electrical appliance line-shape componen, maintains insulation of terminal and joint, binding conducting wire in soft string. The RSG shrinkable tubing is used very conveniently by hating with hot wind gun or oven, it also may be shrunk by hot water which temperate reaches 90



FEATURES

- High soft nature, low contract temperate and high hinder burning character
- Specification is all in readiness: from 1mm to 50mm
- Shrink completely when reaches 90 temperate rang: -30 to 125
- It's installed by spray gun and oven
- Standard colors: black, white, red, yellow, blue and green

Other specifications and colors also can be ordered and be made according to your need

Function level

(Testing level: UL224)



Order No.	Inner Dia.(mm) Max	Inner Dia.(mm) Min	Unit packing (m)
LH010	1.0	0.5	400
LH015	1.5	0.75	300
LH020	2.0	1.0	200
LH025	2.5	1.25	200
LH030	3.0	1.5	200
LH035	3.5	1.75	200
LH040	4.0	2.0	200
LH050	5.0	2.5	100
LH060	6.0	3.0	100
LH070	7.0	3.5	100
LH080	8.0	4.0	100
LH090	9.0	4.5	100
LH100	10.0	5.0	100
LH110	11.0	5.5	100
LH120	12.0	3.0	100
LH130	13.0	6.5	100
LH140	14.0	7.0	100
LH150	15.0	7.5	100
LH160	16.0	8.0	100
LH170	17.0	8.5	100
LH180	18.0	9.0	25
LH200	20.0	10.0	25
LH220	22.0	11.0	25
LH250	25.0	12.5	25
LH280	28.0	14.0	25
LH300	30.0	15.0	25
LH350	35.0	17.5	25
LH400	40.0	20.0	25
LH500	50.0	25.0	25
LH600	60.0	30.0	25
LH700	70.0	35.0	25
LH800	80.0	40.0	25
LH900	90.0	45.0	25